

# Hunter Stativ sprinkler plastik 1/2" indvendig gevind 1,4 - 7,0bar 40°-360° sort type PGJ- 00 (7026340)



**Hunter®**

# TEKNISKE SPECIFIKATIONER

|                           |                              |
|---------------------------|------------------------------|
| Farve                     | sort                         |
| Type                      | PGJ-00                       |
| Materiale                 | plastik                      |
| Kapacitet                 | 0,08 - 1,0 m <sup>3</sup> /t |
| Kapacitet                 | 1,4 - 16,7 l/min             |
| Tilslutning               | indvendig gevind             |
| Sektorjusterbart interval | 40°-360°                     |
| Vinkel                    | 15 °                         |
| Maks. diameter            | 23.2 m                       |
| Radius                    | 4 -10,7 m                    |
| Tryk                      | 1,4 - 7,0 bar                |
| Anbefalet tryk            | 1.7 - 3.8 bar                |
| Størrelse                 | 1/2"                         |

| Type PGJ |      |     |       |      |     |       |      |     |       |      |      |
|----------|------|-----|-------|------|-----|-------|------|-----|-------|------|------|
| 1.0mm    |      |     | 2.0mm |      |     | 3.0mm |      |     | 4.0mm |      |      |
| Bar      | Q    | R   | Bar   | Q    | R   | Bar   | Q    | R   | Bar   | Q    | R    |
| 2.1      | 0.19 | 5.5 | 2.1   | 0.39 | 7.3 | 2.1   | 0.57 | 9.1 | 2.1   | 0.84 | 10.1 |
| 2.8      | 0.23 | 5.8 | 2.8   | 0.45 | 7.6 | 2.8   | 0.68 | 9.4 | 2.8   | 0.91 | 10.4 |
| 3.4      | 0.25 | 5.8 | 3.4   | 0.52 | 7.6 | 3.4   | 0.77 | 9.4 | 3.4   | 1.07 | 10.4 |

# PRODUKTINFORMATION

Standard fabriksinstalleret 2,0 installation af dysehastigheder.

**Genereret den: 24-02-2026**

Bevo Nordic A/S  
Pakhusgården 54  
5000 Odense C  
Danmark  
+45 66 19 25 45  
[info@bevo.dk](mailto:info@bevo.dk)  
<http://www.bevo.com>