

**Hunter Popup-sprinkler plast 1
1/2" utvändig gänga 2,7 -
10,3bar 70° - 360° svart type I-
80-04-SS-ON rostfritt stål
(7032711)**



Hunter®

TEKNISKA SPECIFIKATIONER

Färg	svart
Material	plast
Anslutning	utvändig gänga
Typ	rostfritt stål
Sektorjusterbart intervall	70° - 360°
Riser höjd	9.5 cm
Tryck	2,7 - 10,3 bar
Rek. tryck	3,4 - 6,9 bar
Typ	I-80-04-SS-ON
Kapacitet	4,9 - 13,3 m ³ /h
Kapacitet	81,8 - 221,4 l/min
Storlek	1 1/2"
Radie	19,2 - 29,6 m

PRODUKTINFORMATION

I-80 comes with a gear-driven rotor and has got the most technologically advanced commercial rotor available. Engineered for sports turf and large park applications, the I-80 provides an ultra-robust, dirt-tolerant gear drive that offers the highest torque output of any rotor in the

commercial arena.

Genererad den: 25/02/2026

Bevo Nordic A/S
Pakhusgården 54
5000 Odense C
Danmark
+45 66 19 25 45
info@bevo.dk
<http://www.bevo.com>