

**Tavlit Semi-automatiskt filter
fiberglasförstärkt nylon 2"
utvändig gänga 10bar
120mikron 0,12 mm rostfritt
stål 316 svart type Adir Super
(7028551)**



TEKNISKA SPECIFIKATIONER

Färg	svart
Typ	Adir Super
Material	fiberglasförstärkt nylon
Material filterelement	rostfritt stål 316
Filtrering	120 mikron
Filtrering	120 mesh
Packningsmaterial	EPDM
Anslutning	utvändig gänga
Backspolnings flow rate	5,4 m ³ /h
Längd	280 mm
Vikt	4.5 kg
Min. inloppstryck	2 bar
Tryck	10 bar
Backspolningsuttag	1 "
Kapacitet	25 m ³ /h
Storlek	2"
Filteryta	0.095 m ²

Filtrering 0,12 mm

Höjd 720 mm

PRODUKTINFORMATION

Standard 2 action cleaning system.

Comes with a standard pressure DP indicator that shows the user that the filter is dirty and needs flushing (preset value set to 0.5b).

Flushing is performed by opening the drain valve and rotating the handle.

During flushing, the flow to the field is uninterrupted.

Minimum flushing pressure required: 2bar.

Flushing flow rate: 2bar = 5.4m³/h, 3bar = 6.8m³/h.

We recommend to install a manual valve (open/close) in the upstream.

Genererad den: 23/02/2026

Bevo Nordic A/S
Pakhusgården 54
5000 Odense C
Danmark
+45 66 19 25 45
info@bevo.dk
<http://www.bevo.com>